



Product Service

# CERTIFICATE

No. Z2 115604 0041 Rev. 00

**Holder of Certificate:** **BUGLO Play Sp. z o.o.**  
ul. BoWiD 4  
75-209 Koszalin  
POLAND

**Certification Mark:**



**Product:** **Playground equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713338460-5

**Valid until:** 2029-09-08

**Date,** 2024-09-13

( Tobias Hofmann )

# CERTIFICATE

No. Z2 115604 0041 Rev. 00

**Model(s):** 8401, 8402, 8403, 8404, 8405, 8406, 8407, 8408, 8409, 8410, 8413, 8414, 8415, 8416, 8417, 8418, 8419

## Parameters:

The items are made of robinia poles with inbetween activites like climbing net, climbing rops, climbing poles, balance beams and balance poles.  
The items are mounted on flat or uphill terrain.

| Item Number | Total height (m) | Length (m) | Width (m) |
|-------------|------------------|------------|-----------|
| 8401        | 2.3              | 9.45       | 0.39      |
| 8402        | 2.1              | 11.51      | 2.06      |
| 8403        | 2.1              | 17.28      | 6.69      |
| 8404        | 1.3              | 4.37       | 1.5       |
| 8405        | 2.22             | 2.74       | 1         |
| 8406        | 4.73             | 3.35       | 0.43      |
| 8407        | 3.66             | 4.17       | 0.2       |
| 8408        | 4                | 4.3        | 0.2       |
| 8409        | 1.4              | 2.33       | 0.9       |
| 8410        | 3                | 1.28       | 1.13      |
| 8413        | 1.53             | 4.08       | 4.07      |
| 8414        | 0.4              | 2.4        | 0.2       |
| 8415        | 1.32             | 2.25       | 2.18      |
| 8416        | 0.3              | 0.2        | 0.2       |
| 8417        | 2                | 1.65       | 0.85      |
| 8418        | 1.91             | 3          | 2.05      |
| 8419        | 1.7              | 2.55       | 1.75      |

**Tested according to:**

EN 1176-1:2017/A1:2023